

C2 Slim

Outdoor Standalone Access Control Terminal










IP65 Access Control Device

C2 Slim is the most compact access control device controller which suitable for installing on door frame. It is combined with biometric fingerprint and RFID Card for higher security requirement. Management with master cards, can register or delete users under offline state. The PoE TCP/IP communication will provide more convenient for your project.

















BioNANO - The core algorithm

BioNano is applied in all Anviz biometric-based products used for identification.



- Independent research and development
- Suitable for both wet and dry fingers
- Automatically heals the broken lines in fingerprint images
- Extraction of features in worn fingerprints Fingerprint template auto update

Technical Specifications

Capacity	Fingerprint Capacity	3,000
	Card Capacity	3,000
	Log Capacity	50,000
Interface	Comm.	TCP/IP, RS485
	Relay	1 Relay Output
	I/O	Wiegand Out&In, Door Sensor, Exit Button
Feature	Identification Mode	FP, Card
	Identification Time	<0.5 s
	Webserver	Support
Hardware	CPU	Industrial High Speed CPU
Hardware	CPU Tamper Alarm	Industrial High Speed CPU Support
Hardware		· ·
Hardware	Tamper Alarm	Support
Hardware	Tamper Alarm Sensor	Support Fingerprint Touch activation
Hardware	Tamper Alarm Sensor Scan Area	Support Fingerprint Touch activation 22m*18mm
Hardware	Tamper Alarm Sensor Scan Area RFID Card	Support Fingerprint Touch activation 22m*18mm Standard EM RFID, Optional Mifare/HID Card
Hardware	Tamper Alarm Sensor Scan Area RFID Card Size (W * H * D)	Support Fingerprint Touch activation 22m*18mm Standard EM RFID, Optional Mifare/HID Card 50 * 159 * 25mm







Employee Unify Employee management



Device Quick Add, Easy Setting



Manual and intelligent shift schedule



Export Flexible and Practical Report output

Features

- Small size with compact design
- Easy installation
- New generation sensor hermetic, waterproof and dustproof
- ► BioNANO core fingerprint algorithm: High Performance and Reliability
- Easy user enrollment on the unit via Master Card or in the management software
- ▶ Identification mode: Fingerprint, Card, Fingerprint + Card
- ► Compatible with industrial standard RFID EM & Mifare
- ► Communicate with computer via PoE-TCP/IP and RS485
- Directly connect to lock control and door open sensor as a standalone access controller
- Standard Wiegand26 output
- Various communications(TCP/IP, RS485) are appropriate for multiple network deployment

Network Topology Illustration

